

COMBINED GRAIN DIRECT SEED DRILL (NO-TILL) TRAILED TYPE
Product Details
Combined Grain Direct Seed Drill (No-Till) Trailed Type

No-Till Seed Drill Machine is a modern machine which can directly precision plant seeds of whole grains even in hard soil conditions. Its possible to precision plant seeds such as wheat, barley, oats, rye, large and medium-sized seeds such as rapeseed and small seeds such as clover and canola. This is combined seed drill machine that it can adjust the seed and fertilizer or only seed to desired amount and depth. A reduction in tillage passes helps prevent the compaction of soil. No-till Seeders are used for the raw grain stubble after harvest and fertilizer directly to the desired weight and centimetres (cm) range has the ability to make planting. Using this machine prevents stubble fires, conserves time, labor fuel and water.

Tecnical Features	Units	Models			
		AGS-N18	AGS-N22	AGS-N24	AGS-N28
Number of Discs	pcs	18	22	24	28
Total Length	cm	480	480	480	480
Height	cm	200	200	200	200
Total Width	cm	315	350	385	420
Working Width	cm	238	285	312	369
Seeding Distance	cm	14	14	14	14
Seed Box Capacity	Lt	1050	1180	1300	1450
Fertilizer Box Capacity	Lt	840	950	1050	1175
Working Speed	Km/h	4-8	4-8	4-8	4-8
Weight	kg	3200	3600	3850	4270
Tractor Power	hp	75-85	85-95	95-105	105-115

COMBINED GRAIN DIRECT SEED DRILL (NO-TILL) TRAILED TYPE



OPTIONAL EQUIPMENTS



Extra Tank For Small Seeds



Big Iron Roller