

Fixed Rotovator

Исправлена Почвофреза



Technical Features / Технические Характеристики

		Units	Models / МОДЕЛИ				
			AFR140	AFR160	AFR185	AFR210	AFR240
Total Width	Общая ширина	cm	150	177	202	227	257
Total Length	Общая длина	cm	85				90
Total Height	Общая высота	cm	110				123
Working Depth	Рабочая глубина	cm	22				
Working Width	Рабочая ширина	cm	140	160	185	210	240
Number of Flanges	Количество фланцев	pcs	6	7	8	9	10
Number of Horizontal Blades	Количество горизонтальных лопастей	pcs	30	36	42	48	54
Number of Vertical Blades	Количество вертикальных лопастей	pcs	36	44	52	60	68
P.T.O.	ВОМ	rpm	540				
Tractor Power	Мощность трактора	hp	45-50	50-55	55-60	65-70	70-75
Weight	Вес	kg	390	420	455	490	760



General Features / Общие Характеристики

Fixed Rotovator is a secondary tillage tool used in preparing seed-beds, stubble-ploughing in especially farms, vineyards and gardens.

It is also a multi-purposed and long lasting environment-friendly machine that helps with the increase of the humus content of the soil by incorporating the plant residues and organic fertilizer into the soil and it does not make it a necessity to fight with the chemical weeds.

The fact that the motion coming from the power-take-off shaft is transferred to the blades through the gear system makes savings on power and fuel in proportion to the chain system.

The milling cutter blades shreds, mixes and crumbles the soil by operating vertically on the surface of the soil. It provides the water-air balance of the soil by making it loose.