

HYDRAULIC SHIFTING ROTOVATOR

Product Details

Hydraulic Shifting Rotovator

By the tractor power-take-off shaft and is easily attached to the three-point hitch is a multi-purpose machine that facilitates your works such as preparing the seedling seed-beds, hoeing and the incorporation of organic materials into the soil and aeration of the and as well as preparing seed-beds and stubble-ploughing soil in vineyards and orchards. By the sliding the transmission mechanically it comes much closer to the depths of vine stocks and trees and shreds, mixes and swells the soil well enough. The protection cover which is made from sheet iron ensures that the soil that springs are re-shredded prevents it from harming the surroundings. The machine shafts have a safety arrangement and they prevent the tractor or the machine from being damaged in the event that stones or roots get caught in them.

Tecnical Features	Units	Models			
		AHR165	AHR185	AHR210	AHR240
Total Width	cm	177	202	227	257
Total Length	cm	85	85	85	90
Total Height	cm	105	105	105	123
Working Depth	cm	22			
Working Width	cm	165	185	210	240
Number of Flanges	pcs	7	8	9	10
Number of Horizontal Blades	pcs	36	42	48	54
Number of Vertical Blades	pcs	44	52	60	68
P.T.O.	rpm	540			
Tractor Power	hp	50-55	55-60	65-70	70-75
Weight	kg	415	440	480	760

HYDRAULIC SHIFTING ROTOVATOR

