

## Mounted Turbo Atomizer Смонтированный Турбо Опрыскиватель



### Technical

		MODELS				
	Units	MTA 200	MTA 300	MTA 400	MTA 600	MTA 800
Tank Capacity	Lt.	200	300	400	600	800
Pump	lt/min	A80	A80	A105	A105	A105
Flow Rate	lt/min	80	80	105	105	105
Pressure	bar	50	50	50	50	50
PTO	r/m	540	540	540	540	540
Nozzle		Brass plastic	Brass plastic	brass	brass	brass
Nozzle Pcs	pcs	8	8	10	10	10
Fan Size	cm	60	60	75	75	75
Air Flow Rate	(m3/h)	54000	54000	54000	54000	54000
Length	cm	150	150	150	150	150
Width	cm	105	110	120	140	150
Height	cm	145	150	155	160	165
Weight	kg	230	240	245	255	270
Tractor Power	hp	40-50	40-50	50	50	55



## General Features / Общие Характеристики

Turbo sprayers are used for vineyards, orchards and gardens.

400 and 600 lt. models are tractor mounted on 3-pt hitch by PTO.

Strengthened Fibreglas or Polyethylene depot options

Pump are operated by power takeoff from tractor conveys pressuring chemical liquid to nozzles on fan.

Fan is also operated with power take off and it sends pressured air out.

Pressured chemical liquid is sprayed by adjustable nozzles around the fan by air circulation and any kind of tree can be disinfected.

Fans are operated by two speed transmission.

With separator on the fan, the rotation of the impeller can be prevented.

By setting the angle and direction or by changing the plaque the nozzle on the fan, spraying distance and amount can be adjusted.

By setting the direction of the propeller fan, the air flow can be controlled.

Using distributor valve on the regulator right, left or spraying is done in both directions.

Turbo fan delivers an average shot distance.

- Easily cleanable water fitler
- Easily adjustable and usage
- High efficiency
- Pressure regulation
- Level indicator on the tank
- Clean water tank