

Trailed Turbo Atomizer
Прицепные Турбо Опрыскиватель



Technical

	Units	MODELS		
		TTA 1000	TTA 1600	TTA 2000
Tank Capacity	Lt.	1000	1600	1000
Pump	lt/min	A145	A145	A145
Pressure	bar	50	50	50
PTO	r/m	540	540	540
Nozzle		brass	brass	brass
Nozzle Pcs	pcs	16	16	16
Fan Size	cm	90	90	90
Air Flow Rate	(m3/h)	66000	66000	66000
Length	cm	375	400	428
Width	cm	155	170	180
Height	cm	130	140	150
Weight	kg	510	555	580
Tractor Power	hp	60	60	60



General Features / Общие Характеристики

Turbo sprayers are used for vineyards, orchards and gardens.

1000, 1600 and 2000 lt. models are trailed type by PTO.

Strengthened Fibreglas or Polyethylene depot options

Pump are operated by power takeoff from tractor conveys pressuring chemical liquid to nozzles on fan.

Fan is also operated with power take off and it sends pressured air out.

Pressured chemical liquid is sprayed by adjustable nozzles around the fan by air circulation and any kind of tree can be disinfected.

Fans are operated by two speed transmission.

With separator on the fan, the rotation of the impeller can be prevented.

By setting the angle and direction or by changing the plaque the nozzle on the fan, spraying distance and amount can be adjusted.

By setting the direction of the propeller fan, the air flow can be controlled.

Using distributor valve on the regulator right, left or spraying is done in both directions.

Turbo fan delivers an average shot distance.

- Easily cleanable water fitler
- Easily adjustable and usage
- High efficiency
- Clean water tank
- Pressure regulation
- Level indicator on the tank